Nexans ref.: N521.660BK

- · Compatible with Nexans keystone connectors
- Designed for Essential-5 and -6 range
- 24 ports on 1HU
- Tie wrap strain relief
- · Earthing and grounding features
- Black finish (RAL9011)
- · Also available in white

DESCRIPTION

Application

Nexans modular patch panels for keystone connectors are based on 19" frame dimensions and can accommodate up to 24 keystone connectors on 1U.

Note: LANmark Snap-In connectors need to be equipped with keystone clip (N429.625 or N429.626) to fit into Keystone Panels series.

Design

The patch panels are designed to accomodate 24 keystone connectors.

The metalwork at the back of the panel is made of unpainted steel to enable the necessary earthing and bonding when using shielded cable and connectors. The painted front plate allows a neat flush mounting of the connectors.

The panels have screen-printed numbering 1-24 above the ports and a labelling field at the right end for patch panel numbering or identification.

Installation

The Nexans keystone connectors can easily be latched in place without the need for any tool. They are also easy to remove from the panel, when necessary.

The panels feature rear cable management for tie-wraps to ensure cable retention and strain relief and are supplied with fixings.

STANDARDS

International ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial docu indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans. Generated 07/06/20 www.nexans.co.uk Page 1 / 2



LAN Systems (Nexans Cabling Solutions) Phone: +44 (0)1256 486640 ncs.uk@nexans.com



Contact

Contact

LAN Systems (Nexans Cabling Solutions) Phone: +44 (0)1256 486640 ncs.uk@nexans.com

CHARACTERISTICS

Construction characteristics		
Colour	Black	
Dimensional characteristics		
Heightunit	1 U	
Depth	82 mm	
Usage characteristics		
Packaging	Box	
Dimensional characteristics Heightunit Depth Usage characteristics	1 U 82 mm	

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans. Generated 07/06/20 www.nexans.co.uk Page 2 / 2

