

# LANmark-OF Pigtails Tight Buffer

LANmark-OF Pigtail LC/APC Singlemode Tight Buffer LSZH 9/125 1m Yellow

## Contacto

Ventas Local  
ventas.peru@nexans.com  
exportaciones.peru@nexans.com

Ref. Nexans: N121.4TPY

- Factory terminated fibre assembly
- Tight Buffer pigtail: 1-2cm stripping in one action
- Insertion loss per connection without splice: typical 0,1 dB; 0.25 dB maximum
- 100 % factory tested
- Compatible with LANmark-OF splice cassette with heat shrink protectors

## DESCRIPCIÓN

### Pigtail characteristics

- Fibre assembly to terminate cable with fusion splicing
- Suitable for use in patch panels using splice cassettes
- The pigtails can be stripped in one action over a distance of 1-2cm

### Fibre type


- The LANmark-OF SM pigtails have LANmark-OF SM **GIGAliteFLEX** fibre inside. These fibres are bend insensitive and compliant to ITU-T G.657.A1 and to IEC 60793-2-50, fibre model B6.a1. The pigtail jacket of the singlemode pigtails is yellow.

### Compatibility and installation practices

- Tight buffer pigtails are compatible with heat shrink splice cassettes (N890.090 and N890.095) with heat shrink protections (N890.021).
- Tight buffer pigtails are recommended to be used with tight buffer cables, i.e. with 900 um fibres. When using loose tube cables (250 um fibres) additional stress on the loose tube fibres should be limited as much as possible
- Around the splice area the pigtail needs to be stripped till the cladding before insertion in the splice tool.
- For proper alignment in the fusion splice tool the pigtail is fixed on the 900 um outer sheath. There is no need to strip the outer sheath of the pigtail on the place for fixation for getting a proper fixation.

### Guarantuees

Nexans LANmark-OF pigtails are covered by Nexans warranty as described in the General Terms and Conditions.



# LANmark-OF

## NORMA

Internacional ISO/IEC 11801

# LANmark-OF Pigtails Tight Buffer

LANmark-OF Pigtail LC/APC Singlemode Tight Buffer LSZH 9/125 1m Yellow

## Contacto

Ventas Local  
ventas.peru@nexans.com  
exportaciones.peru@nexans.com

## CARACTERÍSTICAS

### Características de construcción

Tipo de conector	LC/APC
Tipo de Fibra Óptica	SM (G657.A1)

### Características de transmisión

Insertion Loss, maximum, dB	0,25 dB
Return Loss, Minimum, dB	65 dB

## MACROBENDING LOSS SINGLEMODE

	1550 nm	1625 nm
10 turns on a 15 mm radius mandrel	$\leq 0,25$ dB	$\leq 1,0$ dB
1 turns on a 7,5 mm radius mandrel	$\leq 0,75$ dB	$\leq 1,5$ dB